



TRANSFORMER COMPONENTS??
ASK ASCO!!



www.ascocomponents.co.uk

sales@ascocomponents.co.uk

EI 114 V FLANGE (PAT UK120 EQUIVALENT)

Lam 95x114

| TYPE | REF. | a | b | c | d | e | f | g | h | S | L |
|-----------|-----------|------|------|------|------|-------|------|------|------|-----|------|
| EI 114/38 | 3838V/1-2 | 38,8 | 38,0 | 57,0 | 75,0 | 80,0 | 54,5 | 27,0 | 25,0 | 1,5 | 65,0 |
| EI 114/44 | 3844V/1-2 | 38,8 | 44,0 | 57,0 | 75,0 | 87,0 | 54,5 | 27,0 | 25,0 | 1,5 | 65,0 |
| EI 114/50 | 3850V/1-2 | 38,8 | 50,0 | 57,0 | 75,0 | 94,0 | 54,5 | 27,0 | 25,0 | 1,5 | 65,0 |
| EI 114/60 | 3860V/1-2 | 38,8 | 60,0 | 57,0 | 75,0 | 103,0 | 54,5 | 27,0 | 25,0 | 1,5 | 65,0 |
| EI 114/76 | 3876V/1-2 | 38,8 | 76,0 | 57,0 | 75,0 | 121,0 | 54,5 | 27,0 | 25,0 | 1,5 | 65,0 |



TEMPERATURE AND FLAMABILITY RATINGS OF STANDARD MATERIALS

| Material Ref | Base Material | Temperature Class (2000h) | Conforming to standards | UL94 |
|--------------|---------------------------------|---------------------------|---------------------------------|------|
| RP3 | Nylon6 +30% glass reinforced | F (155°C) | IEC85 ASTM ISO/VDE DIN | HB |
| RP5 | Nylon 6.6 +25% glass reinforced | B (130°C) | | V0 |
| RP7 | Pet +30% glass reinforced | H (180°C) | | V0 |