



TRANSFORMER COMPONENTS??
ASK ASCO!!



www.ascocomponents.co.uk

sales@ascocomponents.co.uk

EI 192 V FLANGE (UK 750A EQUIVALENT)

Lam 160x192

| TYPE | REF. | a | b | c | d | e | f | g | h | s | L |
|------------|------------|------|-------|------|-------|-----|------|------|------|-----|-------|
| EI 192/60 | 6460V/1 | 65,5 | 60,0 | 94,5 | 125,3 | 134 | 89,7 | | | 2,3 | 103,0 |
| EI 192/64 | 6464V/1 | 65,5 | 64,0 | 94,8 | 125,5 | 145 | 89,8 | | | 2,3 | 103,0 |
| EI 192/70 | 6470V/1-2 | 65,5 | 70,0 | 94,8 | 125,0 | 146 | 90,0 | 42,0 | 44,9 | 2,2 | 103,0 |
| EI 192/80 | 6480V/1-2 | 65,5 | 80,0 | 94,8 | 125,0 | 156 | 90,0 | 42,0 | 44,9 | 2,2 | 103,0 |
| EI 192/90 | 6490V/1-2 | 65,5 | 90,0 | 94,8 | 125,0 | 166 | 90,0 | 42,0 | 44,9 | 2,2 | 103,0 |
| EI 192/100 | 64100V/1-2 | 65,5 | 100,0 | 94,5 | 125,5 | 176 | 90,0 | 42,0 | 44,5 | 2,2 | 103,0 |
| EI 192/110 | 64110V/1-2 | 65,5 | 110,5 | 94,5 | 125,5 | 186 | 89,7 | 42,0 | 44,5 | 2,2 | 103,0 |
| EI 192/120 | 64120V/1-2 | 65,5 | 120,5 | 94,5 | 125,5 | 196 | 89,7 | 42,0 | 44,5 | 2,2 | 103,0 |
| EI 192/130 | 64130V/1-2 | 65,5 | 130,0 | 94,5 | 126,0 | 206 | 89,7 | 42,0 | 44,5 | 2,2 | 103,0 |
| EI 192/150 | 64150V/1-2 | 65,8 | 149,5 | 94,5 | 126,2 | 226 | 89,7 | 42,0 | 44,5 | 2,2 | 103,0 |



TEMPERATURE AND FLAMABILITY RATINGS OF STANDARD MATERIALS

| Material Ref | Base Material | Temperature Class (2000h) | Conforming to standards | UL94 |
|--------------|---------------------------------|---------------------------|---------------------------------|------|
| RP3 | Nylon6 +30% glass reinforced | F (155°C) | IEC85 ASTM ISO/VDE DIN | HB |
| RP5 | Nylon 6.6 +25% glass reinforced | B (130°C) | | V0 |
| RP7 | Pet +30% glass reinforced | H (180°C) | | V0 |